



SELECTABLE GALLONAGE NOZZLE

03 MNSG-55A (Light Alloy)

03 MNSG-55B (Brass)

Features

- Strong Lightweight Aluminum Alloy or Brass Construction
- Easy selection of flow setting by simply turning of spring loaded baffle head
- Combination Fog and Straight Stream Patterns
- Superior Reach
- Suitable for Water or Foam Application
- Standard inlet size: 1½" female NST



03 MNSG-55A



03 MNSG-55B

Technical Specification

Model	Flow		Material	Inlet Size	Length	Weight
	GPM	litre/min				
03 MNSG-55A	60-95-125	230-360-475	Aluminum Alloy	1½	152 (6.0)	1.2 (2.6)
03 MNSG-55B	60-95-125	230-360-475	Brass	1½	152 (6.0)	3.2 (7.0)

Performance Data

Model	Nozzle Pressure		Flow Setting		Actual Flow		Straight Stream Reach			
	PSI	BAR	GPM	LPM	GPM	LPM	Effective		Overall	
							Feet	Metres	Feet	Metres
03 MNSG-55A 03 MNSG-55B	75	5	60	230	50	190	105	32	120	36
	100	6.9			60	230	110	33	125	38
	125	8.6			69	260	120	36	135	40