

SELECTABLE FLOW NOZZLE

03 MNSG-30A (Anodised Light Alloy)


03 MNSG-30B (Brass)

Features

- Selectable Gallonage
300-500-700 gpm
- Rugged Brass Casting construction
Option: Aluminium Alloy construction
- Combination Fog and Straight Stream
Patterns
- Stainless steel Handles
- Grease Fitting for Easy Maintenance
- Standard inlet size: 2½" female NST
- Excellent for Industrial and Marine
Applications



03 MNSG-30A



03 MNSG-30B

Technical Specification:

Model	Material	Flow		Inlet Size	Length	Weight
		GPM	litre/min	inch	mm (inches)	kg (lbs)
03 MNSG-30A	Aluminium Alloy	300	1,140	2½	178 (7)	2.5 (5.5)
		500	1,900			
03 MNSG-30B	Brass	700	2,660	2½	178 (7)	6.36 (14)

Performance Data:

Model	Flow	Discharge in US GPM			Effective Reach in METRES		
	Straight Stream	Nozzle Pressure PSI			Nozzle Pressure PSI		
	GPM	75	100	125	75	100	125
03 MNSG-30A 03 MNSG-30B	300	260	300	335	45	51	58
	500	435	500	560	53	60	67
	700	605	700	785	55	62	67