



SELECTABLE GALLONAGE NOZZLE

03 MNSG-36A

03 MNSG-36B

Features

- Selectable Gallonage
300-500-800-1000 GPM
- Strong Lightweight Aluminum Alloy or Brass Construction
- Superior Reach and Penetration
- Combination Fog and Straight Stream Patterns
- Stainless steel Handles
- Hard Anodised or Satin Brass Finish
- Grease Fitting for Easy Maintenance
- Standard inlet size: 2½" female NST
- Excellent for Industrial and Marine Applications



04 MN- 36A



03 MNSG-36B

Technical Specification:

Model	Flow		Material	Inlet Size	Length	Weight
	GPM	litre/min				
03 MNSG-36A	300-500-800-1000	1140-1900-3030-3800	Aluminum Alloy	2½"	188 (7.4)	3.0 (6.6)
03 MNSG-36B	300-500-800-1000	1140-1900-3030-3800	Brass	2½"	188 (7.4)	8.6 (19)

Performance Data:

Model	Flow Setting		Actual Flow			Straight Stream Reach		
	Straight Stream		5.0 bar	7.0 bar	8.5 bar	5.0 bar	7.0 bar	8.5 bar
	GPM	litre/min	GPM			metres		
03 MNSG-36A 03 MNSG-36B	300	1,140	260	300	335	46	51	58
	500	1,900	425	500	560	53	60	67
	800	3,030	693	800	894	60	70	76
	1,000	3,800	866	1,000	1,118	67	80	85