



SELECTABLE GALLONAGE NOZZLE

03 MNSG-38A

03 MNSG-38B

Features

- Selectable Gallonage
500-750-1000-1250 GPM
- Strong Lightweight Aluminum Alloy or Brass Construction
- Superior Reach and Penetration
- Combination Fog and Straight Stream Patterns
- Stainless steel Handles
- Hard Anodised or Satin Brass Finish
- Grease Fitting for Easy Maintenance
- Standard inlet size: 2½" female NST
- Excellent for Industrial and Marine Applications



03 MNSG-38A



03 MNSG-38A

Technical Specification:

Model	Flow		Material	Inlet Size	Length	Weight
	GPM	litre/min				
03 MNSG-38A	500-750-1000-1250	1900-2900-3800-4800	Aluminum Alloy	2½	188 (7.4)	3.0 (6.6)
03 MNSG-38B	500-750-1000-1250	1900-2900-3800-4800	Brass	2½	188 (7.4)	8.6 (19)

Performance Data:

Model	Flow Setting		Actual Flow in GPM			Straight Stream Reach		
	Straight Stream		5.0 bar	7.0 bar	8.5 bar	5.0 bar	7.0 bar	8.5 bar
	GPM	litre/min	GPM			m		
03 MNSG-38A 03-MNSG-38B	300	1,900	433	500	560	53	67	71
	750	2,840	650	750	839	59	73	77
	1,000	3,800	866	1,000	1,118	67	79	82
	1,250	4,800	1,083	1,250	1,398	71	83	86